

BTP-T150

TICKET printer 56mm

HEAVY DUTY CUTTER

www.orient-technologies.com



Standard features at a glance:

- High speed ticket printing(100mm/s)
- With special heavy duty auto cutter for thick paper solution
- Suitable for up to 0.25mm thickness ticket
- With pick up box for collecting tickets
- All metal compact design
- Supports continuous paper and marked paper
- Easy and fast paper loading



ORIENT Technologies bv a subsidiary of SNBC of Weihai/China **SNBC**[®]

ORIENT Technologies b.v.
Meerheide 115, 5521 DX Eersel, The Netherlands
Phone +31 (0)497 331080, Fax +31 (0)497 386430

BTP-T150

Ticket printer 56mm

Print

Print method	Line Direct thermal
Resolution	203 DPI
Print width	56 mm (Max.)
Print speed	100 mm/s (Max.)
Memory	64 KB RAM, 1 MB FLASH (Optional: 2 MB / 4 MB)
Sensor	Paper end, black mark, print head open and print head overheating protection
Driver	Windows Drivers (Win98 / NT / 2000 / XP / 2003 / VISTA)
Interfaces	Serial / Parallel / USB

Barcode Fonts Graphics

Barcode	UPC-A, UPC-E, EAN-8, EAN-13, CODABAR, CODE39, ITF, CODE128, CODE93;
Fonts	Font A (12 x 24), Font B (9 x 17), Big font (24 X 24)
Character modification	Rotate (0°, 90°, 180°, 270°), underline, emphasize, reverse, enlarge (1-6X)
Graphics	BMP bitmap can be downloaded to RAM or FLASH

Paper

Paper type	Continuous paper, Marked paper, Folded paper
Paper thickness	0.08 ~ 0.25 mm
Paper width	50 ~ 60 mm
Paper roll	Paper roll external

Power supply

Input	100~240 VAC, 50~60 Hz
Output	24V ± 5%, 2.5A (Printing duty 12.5%)

Reliability

Printhead lifetime	50 km (continuous paper)
Cutter lifetime	500,000 cuts

Environment

Operating conditions	5°C to 45°C, 20% to 90% RH (40°C)
Storage conditions	-40°C to 60°C, 20% to 93% RH (40°C)

Physical spec.

Dimensions	185 (W) x 239 (D) x 153 (H) mm
Weight	Approx. 3.5 kg



ORIENT Technologies bv
Meerheide 115, 5521 DX Eersel, The Netherlands
Phone: +31 (0)497 331080, Fax: +31 (0)497 386430
www.orient-technologies.com

The specifications are subject to change without notice and shall not be regarded as a warranty. All product and company names are trademarks, service marks or registered trademarks of their respective owners.